

Job Name _____

Location _____

Arch./Engr. _____

Wholesaler _____

Mech. Contractor _____

Model No. _____

BTU/hr Input _____

Recovery Rate in GPH _____ °F Rise

Notes _____

High kW/Large Tank ASME Electric Water Heaters:

- 150 to 2500 gallon tank options
- 12kW to 360kW inputs available
- 150 psi ASME code glass-lined tank
- ASME temperature and pressure relief
- Internal fusing (above 120 amps)
- Incoloy heating elements
- Painted steel jacket
- Magnesium anode rods
- Immersion thermostats
- Magnetic contactors
- Digital temperature display
- Manual reset high limit
- Hinged door with keyed lock
- Channel iron skid base
- Approved for 180°F operation
- Lift lug access



150 to 2500 Gallon
 12 to 360kW
 Round Vertical Models
 Outstanding Safety Features



Ultonium Glass Lining = 3 Year Limited Tank Warranty

Double Ultonium Glass Lining = 6 Year Limited Tank Warranty

For products installed in USA, Canada and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

High kW/Large Tank ASME Electric Water Heaters

Standard Equipment Features

Energy-Saving Performance - High-density closed cell foam insulation is used to meet the demanding ASHRAE 90.1b current standard for minimizing heat loss. This requirement, allowing a maximum 4 watts per square foot of tank surface energy loss, offers big savings and operating efficiency.

Magnetic Contactors with Immersion Thermostats - 120 volt control circuit with built in transformer. Elements are thermo-statically controlled in 54kW (max) increments.

Low Watt Density Incoloy Elements - Incoloy elements are used by Bock Steel because of their many superior characteristics to copper-sheathed elements in rigorous water heating applications. This tough alloy successfully resists the effects of prolonged high operating temperatures, hard water, acids, corrosion and thermal shock. Their nominally higher initial cost is more than off-set by much longer life expectancies and reduced service and replacement costs. Incoloy elements are designed to "burn in air" to prevent failures caused by water void.

Internal Fusing - All elements and circuits are fused in 48 amp increments, providing complete electrical protection. Cartridge type fuses are rated at 200,000 ampere interrupting capacity.

Glass-Lined Tank - Porcelain glass is applied to the inside surface of the steel tank and fired to 1600°F. (All models are constructed in accordance with the ASME code and approved for 150 psi working pressure).

Digital Temperature Display - Easy to read digital temperature display located on front cabinet.

Magnesium Anode Protection - Provides anodic protection against corrosion of the tank due to electrolysis.

Painted Jacket - Polyester painted steel jacket is coated on both sides and beautifully finished in durable finish. This combines attractive appearance with maximum protection.

Hinged Door with Key Lock - Quality requires full length hinged doors for ease of inspection and maintenance. Keyed door lock provides additional safety and security at no charge.

Temperature and Pressure Relief Valve - Factory provided ASME rated relief valve protects against excessive temperature and/or pressure buildup within the tank.

Terminal Block Connections - Easy and safe wiring connections are made possible by factory installed terminal blocks.

180°F Temperature Operation - Every Electric Power Water Heater is approved for 180°F operation for sanitizing and other high-temperature requirements.


Inspection Opening - Provides easy access to the heater interior for inspection and cleaning.

Three-Year Limited Warranty - Provides warranty protection against tank failure resulting from defects in material and workmanship.

Lifting Lugs Access - Removable access panels to lifting lugs.

Channel Iron Skid Base

High kW/Large Tank ASME Electric Water Heaters



* = Voltage kW = Kilowatt

Model Number	Gallon Capacity	Maximum kW	A	B	C	DE	Back of Heater to Hot Water Outlet	Water Connection	Approx. Ship Weight
			Floor to Top of Heater	Jacket Dia.	Floor to Cold Water Inlet	Depth			
LVE150 - *(kW)	150	90	67 1/2"	32	12.75"	38 3/4"	16"	1 1/2"	650
LVE200 - *(kW)	200	162	80"	32	12.75"	38 3/4"	17"	1 1/2"	750
LVE250 - *(kW)	250	162	92"	34	16.88"	40 3/4"	17"	1 1/2"	1165
LVE300 - *(kW)	300	162	80"	40	19.25"	40 3/4"	20"	2"	1350
LVE400 - *(kW)	400	216	80"	46	19.75"	52 3/4"	23"	2"	1590
LVE500 - *(kW)	500	216	92"	46	19.75"	52 3/4"	23"	2"	1700
LVE600 - *(kW)	600	216	92"	52	21.75"	58 3/4"	26"	2 1/2"	2010
LVE800 - *(kW)	800	270	104"	52	21.75"	58 3/4"	26"	2 1/2"	2450
LVE1000 - *(kW)	1000	360	128"	52	21.75"	58 3/4"	26"	2 1/2"	3160
LVE1250 - *(kW)	1250	360	133"	58	25.75"	64 3/4"	29"	3"	3792
LVE1500 - *(kW)	1500	360	129"	64	27.25"	70 3/4"	32"	3"	4550
LVE2000 - *(kW)	2000	360	140"	70	28.50"	76 3/4"	35"	3"	5460
LVE2500 - *(kW)	2500	360	144"	76	30.25"	82 3/4"	38"	3"	6553

*Note: Vertical round models above 90kW at 208V, 240V or 380V, and 162kW at 400V or 480V, exceed the capacity of a single control panel and may require multiple control panels. Consult the factory for specific details and optional construction.



Available Voltages

A - 240V, 1ph	K - 208V, 3ph	X - 480V, 3ph	Z - 415V, 3ph
B - 240V, 3ph	Q - 400V, 3ph	Y - 380V, 3ph	N - 600V, 3ph
J - 208V, 1ph	W - 277V, 1ph		



Submittal Sheet

High kW/Large Tank ASME Electric Water Heaters

Commercial Electric Water Heaters

For kW inputs not shown, consult factory.

*380V has 4

**380V has 6

***380V has 8

****380V has 9

Standard kW Input and Amperage

kW	GPH Recovery 100 F Rise	BTU/hr. Equivalent	Number of Control Steps	Maximum Number of Elements	kW Size of Element	Contactor Option		Amperage Draw								
						No. of Contactors (208,240)/(380,400,415,480)	Suggested Control Steps (208, 240)/(380,400,415,480)	Single	Phase	Three Phase						
										208V	240V	208V	240V	380V	400V	415V
12	49	40,944	1	1	12	1/1	--	58	50	33	29	19	17	17	14	12
15	62	51,180	1	1	15	1/1	--	72	63	42	36	23	22	21	18	14
18	74	61,416	1	1	18	2/1	--	87	75	50	44	28	26	25	22	17
30	123	102,360	1	2	15	2/1	--	144	125	83	72	46	44	42	36	29
36	148	122,832	1	2	18	4/2	4/2	174	150	100	87	55	51	50	43	35
45	185	153,540	1	3	15	3/2	3/2	216	188	125	108	69	66	63	54	43
54	221	184,248	1	3	18	6/2	3/2	260	225	150	130	83	78	75	65	52
60	246	204,720	2	4	15	12/6	4/3	289	250	167	144	92	88	83	72	58
72	295	245,664	2	4	18	8/4	4/4	--	--	200	174	110	104	100	87	69
90	369	307,080	2	6	15	6/3*	3/3	--	--	250	217	137	132	125	108	87
108	443	368,496	2	6	18	12/4**	4/4	--	--	300	260	165	156	150	130	104
120	492	409,440	3	8	15	8/4***	4/4	--	--	333	289	183	176	167	144	115
135	554	460,620	3	9	15	9/6	4/4	--	--	375	325	206	198	188	162	130
144	590	491,328	3	8	18	16/8	4/4	--	--	400	347	219	208	200	173	139
162	664	552,744	3	9	18	18/6****	8/6	--	--	450	389	247	234	225	195	156
180	738	614,160	4	10	18	20/10	8/8	--	--	500	434	273	260	250	217	173
216	886	736,992	4	12	18	24/8	8/8	--	--	600	519	328	312	301	260	208
234	959	798,408	5	13	18	26/13	8/8	--	--	650	563	355	338	326	282	225
252	1033	859,824	5	14	18	28/14	12/10	--	--	700	607	383	364	351	304	242
270	1107	921,240	5	15	18	30/10	12/12	--	--	750	649	410	390	376	325	260
288	1181	982,656	6	16	18	32/16	12/12	--	--	800	692	438	416	401	347	277
306	1256	1,044,072	6	17	18	34/17	12/12	--	--	850	736	465	442	426	368	294
324	1328	1,105,488	6	18	18	36/12	12/12	--	--	900	780	492	468	451	390	312
342	1402	1,166,904	7	19	18	38/19	12/12	--	--	950	822	520	494	476	412	329
360	1476	1,228,320	7	20	18	40/20	12/12	--	--	1,000	865	547	520	501	435	346

Typical Specifications

Water Heaters shall be BOCK Electric Water Heater model number _____ ,

with _____ gallons of storage capacity, rated at _____ Kilowatts, _____ Volts, _____ Phase.

Heater to be completely insulated and jacketed for vertical installation.

The jacket shall be round painted steel with durable finish. Control panel shall have a full length hinged access door with keyed lock. Tank insulation shall be closed cell high density foam sufficient to meet ASHRAE 90.1b. Keyed locked door provides additional safety and security.

Tank construction shall be 150 psi maximum allowable working pressure and be ASME stamped and National Board listed. All tanks are to be lined with Porcelain superior glass lining, fired at 1600°F (871°C) by a process which provides a molecular interchange of glass and steel. High kW/Large Volume ASME Electric shall include the following standard features: magnetic contactors with immersion thermostats, digital temperature display, internal fusing for control and load circuits, low-watt density Incoloy sheath elements, magnesium anode rods, ASME rated temperature and pressure relief valve, terminal block wiring, 180°F (82°C) water temperature approval, 3-year limited warranty.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.